

AMENDMENTS TO THE CLAIMS

1. (Currently amended) A garment pad kit for coupling a garment pad to a garment, the garment pad kit comprising;

(a) a garment pad including a body portion having an inner surface and an outer adhering surface, wherein the body portion is three-dimensionally dome shaped to correspond to a breast region or shoulder region of a user;

~~(b) an adhesive for coupling the outer adhering surface to a garment; and~~

[[~~(c)~~]] (b) a portion of bonding fabric adapted to be disposed between the garment pad and a garment by the user, ~~wherein the adhesive is disposed upon the portion of bonding fabric and~~ wherein the bonding fabric includes a relief gap disposed in the portion of bonding fabric for assisting in forming the portion of bonding fabric from a substantially planar configuration to an areuate a partial dome shaped configuration; and

(c) an adhesive disposed on a portion of the bonding fabric, the adhesive adapted to couple the portion of bonding fabric to a garment when the bonding fabric is disposed between the garment pad and a garment by the user.

2. (Canceled)

3. (Currently amended) The garment pad kit of Claim 1, wherein the adhesive is a temperature sensitive adhesive, wherein the temperature sensitive adhesive is adapted to permanently couple the garment pad to a garment when the temperature sensitive adhesive is heated ~~above a selected temperature~~.

4-6. (Canceled)

7. (Currently amended) A garment pad kit for coupling a garment pad to a garment, the garment pad kit comprising;

(a) a garment pad including a body portion having an inner surface and an outer adhering surface, wherein the body portion is three-dimensionally dome shaped to correspond to a breast region or shoulder region of a user;

~~(b) an adhesive for coupling the outer adhering surface to a garment; and~~

[[~~(c)~~]] (b) a portion of bonding fabric adapted to be disposed between the garment pad and a garment by the user, ~~wherein the adhesive is disposed upon the portion of bonding fabric and~~ wherein the portion of bonding fabric includes a series of relief cuts for assisting in forming the portion of bonding fabric from a substantially planar configuration to an areuate a partial dome shaped configuration; and

(c) an adhesive disposed on a portion of the bonding fabric, the adhesive adapted to couple the portion of bonding fabric to a garment when the bonding fabric is disposed between the garment pad and a garment by the user.

8. (Currently amended) A garment pad kit for coupling a garment pad to a garment, the garment pad kit comprising;

(a) a garment pad including a body portion having an inner surface and an outer adhering surface, wherein the body portion is three-dimensionally dome shaped to correspond to a breast region or shoulder region of a user;

~~(b) an adhesive for coupling the outer adhering surface to a garment; and~~

[[~~(c)~~]] (b) a portion of bonding fabric adapted to be disposed between the garment pad and a garment, ~~wherein the adhesive is disposed upon the portion of bonding fabric and~~ wherein the portion of bonding fabric includes an aperture for assisting in forming the

portion of bonding fabric from a substantially planar configuration to ~~an areuate~~ a partial dome shaped configuration; and

(c) an adhesive disposed on a portion of the bonding fabric, the adhesive adapted to couple the portion of bonding fabric to a garment when the bonding fabric is disposed between the garment pad and a garment by the user.

9. (Currently amended) A garment pad for coupling a garment pad to a garment, the garment pad kit comprising;

(a) a garment pad including a body portion having an inner surface and an outer adhering surface, wherein the body portion is three-dimensionally dome shaped to correspond to a breast region or shoulder region of a user;

~~(b) an adhesive for coupling the outer adhering surface to a garment; and~~

[[~~(c)~~]] (b) a portion of bonding fabric adapted to be disposed between the garment pad and a garment, ~~wherein the adhesive is disposed upon the portion of bonding fabric~~ and wherein the portion of bonding fabric includes a relief gap, a series of relief cuts, and an aperture for assisting in forming of the portion of bonding fabric from a substantially planar configuration to ~~an areuate~~ a partial dome shaped configuration; and

(c) an adhesive disposed on a portion of the bonding fabric, the adhesive adapted to couple the portion of bonding fabric to a garment when the bonding fabric is disposed between the garment pad and a garment by the user.

10. (Currently amended) The garment pad kit of Claim 1, wherein the adhesive is a piece of double-sided tape having adhesive disposed on a first side and a second side of a ~~piece of double-sided tape~~ non-adhesive tape strip, ~~the double-sided tape adapted to be disposed between the garment pad and a garment for adhering the garment pad to the garment.~~

11. (Currently amended) A garment pad kit for coupling a garment pad to a garment, the garment pad kit comprising;

(a) a garment pad including a body portion having an inner surface and an outer adhering surface, wherein the body portion is three-dimensionally dome shaped to correspond to a breast region or shoulder region of a user; and

(b) an adhesive for coupling the outer adhering surface to a garment wherein the adhesive is disposed on a first side and a second side of a piece of double-sided tape, a piece of double-sided tape having adhesive disposed on a first side and a second side of a non-adhesive tape strip, the piece of double-sided tape adapted to be disposed between the garment pad and a garment by a user for adhering the garment pad to the garment and wherein the piece of double-sided tape is arcuate in shape when in a planar configuration.

12. (Currently amended) A garment pad kit for coupling a garment pad to a garment, the garment pad kit comprising;

(a) a garment pad including a body portion having an inner surface and an outer adhering surface, wherein the body portion is three-dimensionally dome shaped to correspond to a breast region or shoulder region of a user; and

(b) an adhesive for coupling the outer adhering surface to a garment wherein the adhesive is disposed on a first side and a second side of a piece of double-sided tape, a piece of double-sided tape having adhesive disposed on a first side and a second side of a non-adhesive tape strip, the piece of double-sided tape adapted to be disposed between the garment pad and a garment by a user for adhering the garment pad to the garment and wherein the piece of double-sided tape includes a series of relief cuts for assisting in forming the piece of double-sided tape from a substantially planar configuration to an arcuate a partial dome shaped configuration.

13-26. (Canceled)

27. (Currently amended) A garment pad adapted to be selectively coupled to a garment, the garment pad comprising:

(a) a body having an inner surface and outer adhering surface, wherein the body is three-dimensionally dome shaped to correspond to a breast region or shoulder region of a user; and

~~(b) — an adhesive disposed on the outer adhering surface of the body; and~~

[[~~(c)~~]] (b) a support layer adhered to the outer adhering surface, the support layer having a first surface and a second surface, wherein a pressure sensitive adhesive is disposed upon the first and second surfaces, wherein the support layer includes a relief gap for assisting in forming of the support layer from a substantially planar configuration to ~~an arcuate a~~ partial dome shaped configuration.

28. (Currently amended) The garment pad of Claim 27, wherein ~~the adhesive is a~~ said pressure sensitive adhesive is adapted to temporarily couple the garment pad to a garment when subjected to a pressure ~~above a selected pressure~~.

29. (Currently amended) The garment pad of Claim 27, wherein the pressure sensitive adhesive is a temperature sensitive material disposed on the outer adhering surface of the body, wherein the temperature sensitive material is adapted to permanently couple the garment pad to a garment when the temperature sensitive material is heated ~~above a selected~~ temperature.

30-31. (Canceled)

32. (Currently amended) A garment pad adapted to be selectively coupled to a garment, the garment pad comprising:

(a) a body having an inner surface and outer adhering surface, wherein the body is three-dimensionally dome shaped to correspond to a breast region or shoulder region of a user; and

~~(b) — an adhesive disposed on the outer adhering surface of the body; and~~

[[~~(c)~~]] (b) a support layer adhered to the outer adhering surface, the support layer having a first surface and a second surface, wherein a pressure sensitive adhesive is disposed upon the first and second surfaces, and wherein the support layer includes a series of relief cuts for assisting in forming of the support layer from a substantially planar configuration to ~~an areuate~~ a partial dome shaped configuration.

33. (Currently amended) A garment pad adapted to be selectively coupled to a garment, the garment pad comprising:

(a) a body having an inner surface and outer adhering surface, wherein the body is three-dimensionally dome shaped to correspond to a breast region or shoulder region of a user; and

~~(b) — an adhesive disposed on the outer adhering surface of the body; and~~

[[~~(c)~~]] (b) a support layer adhered to the outer adhering surface, the support layer having a first surface and a second surface, wherein a pressure sensitive adhesive is disposed upon the first and second surfaces, and wherein the support layer includes an aperture for assisting in forming of the support layer from a substantially planar configuration to ~~an areuate~~ a partial dome shaped configuration.

34. (Currently amended) A garment pad adapted to be selectively coupled to a garment, the garment pad comprising:

(a) a body having an inner surface and outer adhering surface, wherein the body is three-dimensionally dome shaped to correspond to a breast region or shoulder region of a user; and

~~(b) —an adhesive disposed on the outer adhering surface of the body; and~~

[[~~(c)~~]] (b) a support layer adhered to the outer adhering surface, the support layer having a first surface and a second surface, wherein a pressure sensitive adhesive is disposed upon the first and second surfaces, and wherein the support layer includes a relief gap, a series of relief cuts, and an aperture for assisting in forming of the support layer from a substantially planar configuration to ~~an arcuate~~ a partial dome shaped configuration.

35. (Currently amended) A garment pad adapted to be selectively coupled to a garment, the garment pad comprising:

(a) a body having an inner surface and outer adhering surface, wherein the body is three-dimensionally dome shaped to correspond to a breast region or shoulder region of a user; and

~~(b) —an adhesive disposed on the outer adhering surface of the body; and~~

[[~~(c)~~]] (b) a support layer adhered to the outer adhering surface, the support layer having a first surface and a second surface, wherein a pressure sensitive adhesive is disposed upon the first and second surfaces, and wherein the support layer includes a plurality of panels coupled to one another to configure the support layer in ~~an arcuate~~ a partial dome shaped configuration.

36. (Original) The garment pad of Claim 27, wherein the garment pad is a bra pad or a shoulder pad.

37-38. (Canceled)

LAW OFFICES OF
CHRISTENSEN O'CONNOR JOHNSON KINDNESS^{PLLC}
1420 Fifth Avenue
Suite 2800
Seattle, Washington 98101
206.682.8100